

# ALUMINUM ELECTROLYTIC CAPACITORS

## RADIAL LEAD TAPING

Lead Taping Capacitors for Automatic Insertion

■ STANDARD

Code	Case range		Dimensions				Form	External form Drawing	Packing Form
	$\phi D$	L (max)	H $\pm 0.75$	Ho $\pm 0.5$	F $\pm 0.5$	P $\pm 0.1$			
TB	4~6	5~13	18.5	--	2.5	12.7	A		Flat Box 
	8	5~13	18.5	--	3.5	12.7	A		
	4~8	5~7	17.5	16	5.0	12.7	B		
	5~6.3	11~13	18.5						
	8	11~22	20.0						
	10	11~22	18.5	--	15.0	A			
	12.5	16~27	18.5	--					
16~18	20~27	18.5	--	7.5	30.0	C			

## LEAD CUT AND FORMING

Lead Configuration: FC ( $\phi 4, 5, 6, 3, 8$ ) 	Lead Configuration: FM ( $\phi 4, 5, 6, 3, 8$ ) 	Lead Configuration: ( $\phi 3, 4, 5, 6, 3, 8$ ) 						
Lead Configuration: CC ( $\phi 10, 12.5, 16, 18$ ) 	Lead Configuration: MC ( $\phi 10, 12.5, 16, 18$ ) <table border="1"> <thead> <tr> <th><math>\phi D</math></th> <th>f<math>\pm 0.1</math></th> </tr> </thead> <tbody> <tr> <td><math>\phi 10, 12.5</math></td> <td>1.1</td> </tr> <tr> <td><math>\phi 16, 18</math></td> <td>1.3</td> </tr> </tbody> </table>	$\phi D$	f $\pm 0.1$	$\phi 10, 12.5$	1.1	$\phi 16, 18$	1.3	Lead Configuration: ( $\phi 3, 4, 5, 6, 3, 8$ ) 
$\phi D$	f $\pm 0.1$							
$\phi 10, 12.5$	1.1							
$\phi 16, 18$	1.3							