

List of Products



ALUMINUM ELECTROLYTIC CAPACITORS

	Series	Description	Terminal Type	Load Life(hrs)	Temp. Range (° C)	Capacitance Range (µF)	Voltage Range (V)	Page
Super Chip	CDVS	5.5mm Height	Chip	2000	-40 ~ +85	0.1 ~ 1500	4 ~ 100	13
	CDVB	Bi-polarized	Chip	2000	-40 ~ +85	0.1 ~ 100	6.3 ~ 50	15
	CDVH	5.5mm Height, Wide Temp.	Chip	2000	-55 ~ +105	0.1 ~ 1000	4 ~ 50	17
Super Miniature	CD50S	5mm height	Radial	1000	-40 ~ +85	0.1 ~ 470	4 ~ 50	19
	CD50BP	5mm height, Bi-Polarized	Radial	1000	-40 ~ +85	0.1 ~ 47	6.3~ 50	21
	CD50H	5mm height, Wide Temp.	Radial	1000	-55 ~ +105	0.1 ~ 220	6.3~ 50	22
	CD50Z	5mm Height, Low Impedance, Wide Temp.	Radial	2000	-55 ~ +105	1 ~ 100	6.3~ 35	23
	CD11CX	7mm height	Radial	1000	-40 ~ +85	0.1 ~ 470	4 ~ 100	24
	CD11CH	7mm height, Wide Temp.	Radial	2000	-55 ~ +105	0.1 ~ 220	6.3 ~ 63	26
	CD71C	7mm height Bi-polarized	Radial	1000	-40 ~ +85	0.1 ~ 100	6.3 ~ 50	28
Miniature	CD110	Standard	Radial	2000	-40 ~ +85	0.1 ~ 22,000	6.3 ~ 450	29
	CD110X	Standard	Radial	2000	-40 ~ +85	0.1 ~ 22,000	6.3 ~ 450	29
	CD268	Wide Temp.	Radial	2000	-40 ~ +105	0.1 ~ 10,000	6.3 ~ 450	31
	CD265	Wide Temp.	Radial	1000	-40 ~ +125	0.47 ~ 1,000	10 ~ 100	33
	CD269	Long-life, Wide Temp.	Radial	2000	-40 ~ +125	0.47 ~ 3,300	10 ~ 350	35
	CD11H	For Electronic Ballast	Radial	2000	-40 ~ +105	1~330	160~ 450	37
	CD11A	For Hi-Fi Audio	Radial	2000	-40~ +85	0.47 ~ 15,000	6.3 ~ 100	40
	CD113	Low Loss (dissipation factor)	Radial	1000	-40 ~ +85	0.1 ~ 4,700	6.3 ~ 100	42
	CD113H	Low Loss, Wide Temp.	Radial	1000	-40 ~ +105	0.1 ~ 4,700	6.3 ~ 100	42
	CD117	Low Leakage Current, Low Loss, High Stability	Radial	1000	-40 ~ +85	0.47 ~ 47	10 ~ 50	44
	CD117H	Low Leakage Current, Low Loss, High Stability, Wide Temp.	Radial	1000	-40 ~ +105	0.47 ~ 47	10 ~ 50	44
	CD288	Hi- freq, Low Impedance	Radial	1000	-40 ~ +85	4.7 ~ 3,300	10 ~ 250	45
	CD288H	Hi- freq, Low Impedance, Wide Temp.	Radial	1000	-40 ~ +105	4.7 ~ 3,300	10 ~ 250	45
	CD288HL	Hi- freq, Low Impedance, long life, Wide Temp.	Radial	3000	-55 ~ +105	0.47 ~ 15,000	6.3 ~ 450	47
	CD26L	Low impedance, Long Life, Wide Temp.	Radial	2000	-55 ~ +105	0.1 ~ 15,000	6.3 ~ 400	51
	CD26H	Long Life, Wide Temp.	Radial	5000	-40 ~ +105	1 ~ 10,000	6.3 ~ 450	53
	CD26J	For Energy Saving Lamp	Radial	2000	-40 ~ +105	1 ~ 33	200 ~ 400	55
	CD267	For switching adapter	Radial	2000	-55 ~ +105	56~ 33,000	6.3 ~ 450	56
	CD264	Long life, For Electronic Ballast Power supply	Radial	3000	-40 ~ +105	1.0~ 220	160~ 450	59
	CD266	Long life, For Electronic Ballast Power supply	Radial	5000	-40 ~ +105	1.0~ 220	160~ 450	62
	CD261	Long life, For Electronic Ballast	Radial	8000~10000	-25 ~ +105	6.8~ 220	160~ 450	65
CDME	Wide Temp., Low Impedance, Long Life	Radial	5000	-40 ~ +105	0.47 ~ 15000	6.3 ~ 100	68	

List of Products



ALUMINUM ELECTROLYTIC CAPACITORS

	Series	Description	Terminal Type	Load Life(hrs)	Temp. Range (° C)	Capacitance Range (uF)	Voltage Range (V)	Page
Miniature	CD71	Standard, Bi-polarized	Radial	2000	-40 ~ +85	0.1 ~ 4,700	6.3 ~ 160	70
	CD71H	Bi-polarized, Wide Temp.	Radial	1000	-40 ~ +105	0.47 ~ 6,800	6.3 ~ 100	72
	CD72	Bi-polarized for Speaker Network	Radial	1000	-40 ~ +85	1 ~ 100	50	74
	CD72H	Bi-polarized for Speaker Network, Wide Temp.	Radial	1000	-40 ~ +105	1 ~ 100	50	74
	CDS	Horizontal Deflection	Radial	1000	-40~ +85	1 ~15	25 ~ 100	75
	CDSH	For Horizontal Deflection, Wide Temp.	Radial	1000	-40 ~ +105	1 ~15	25 ~ 100	75
	CD95	Miniature, Long-life	Axial	2000	-40 ~ +85	0.47 ~ 10,000	6.3 ~ 160	76
	CD95B	Bi-polarized, Long-life	Axial	2000	-40 ~ +85	0.1 ~ 4,700	6.3 ~ 160	78
Large Size	CD292	High Reliability	Snap-in (4 pins)	2000	-40 ~ +85	180 ~82,000	10 ~450	79
	CD293	Standard	Snap-in	2000	-40 ~ +85	68 ~ 82,000	10 ~ 450	81
	CD294	High Ripple Current, Wide Temp.	Snap-in	2000	-40~ +105	39 ~ 47,000	16 ~ 450	83
	CD295	Long Life	Snap-in	3000	-40~ +85	39 ~ 22,000	16 ~ 450	85
	CD296	Long Life, Wide Temp.	Snap-in	3000	-40 ~ +105	39 ~ 22,000	10~ 400	87
	CD297	High Ripple Current, Long Life	Snap-in	5000	-40 ~ +85	68 ~ 22,000	10 ~ 450	90
	CD298	Long Life ,Wide Temp.	Snap-in	5000	-40 ~ +105	68 ~ 56,000	10~ 450	93
	CD92	Low Voltage, Large Capacity, Low Loss, High Ripple Current	Screw	1000	-40~ +85	2200 ~ 470,000	10 ~ 100	96
	CD92H	Low Voltage, Large Capacity, Low Loss, High ripple, Wide Temp.	Screw	1000	-40 ~ +105	2200 ~ 470,000	10 ~ 100	96
	CD92L	Long Life, High Ripple Current, Extremely Low Impedance	Screw	2000	-40~ +85	1000 ~220,000	10 ~ 100	98
	CD13N	Medium and High Voltage, Large Capacitance, High Ripple Current	Screw	2000	-40 ~ +85	220 ~ 18,000	160 ~ 450	100
	CD13NH	High Ripple Current, Wide Temp.	Screw	2000	-40 ~ +105	270 ~ 390,000	160 ~450	101
	CD13L	Long Life, High Ripple Current	Screw	5000	-40 ~ +85	1000 ~18,000	350 ~450	103
	CD13HL	Long Life, Wide Temp.	Screw	5000	-40 ~ +105	1000 ~15,000	350,400,450	105
	CD98SK	For Car Audio	Screw	3000	-40 ~ +85	0.5F~2F	16,20,25	107
	CDIN	For Air Conditioner	Fast-On	2000	-25 ~ +85	220 ~ 2,500	250 ~ 450	108
	CD60	For Motor Starting	Lug	75000times	-20 ~ +70	25 ~500	110 ~330 VAC	109
Photo Flash	CD17S	For photo flash	Radial		-20~ +55	40 ~300	330~360	110
	CD17FX	For photo flash	Lug		-20~ +55	150 ~1500	330~360	111